

## DTCM110-100H-AL

## C-mount Bi-telecentric Lens

- Optimized for 1/2.5"~1.1" C-Mount cameras;
- Largest FOV from 26mm upto 300mm;
- Excellent resolution for high pixel cameras;
- Low distortion, good telecentricity, big aperture and big depth of field for high end application.

Optical Specifications	
Magnification (x)	0.166
Object Field of View (Фmm)	100
Working Distance (mm)	238±4
Max Sensor Size (Фmm)	16.6(1")
Best Aperture (F/#)	6.5
Telecentricity typical (max) (deg)	<0.1
Distortion typical (max) (%)	<0.1
MTF30 (lp/mm)	>140
Depth of Field (mm)	±23.2@F16
Length of I/O (mm)	534±4



Field of View (mm × mm)		
1" PYTHON 5000(12.43x9.83)	74.9x59.2	
1" IMX255(14.19x7.51)	85.5x45.2	
1" IMX183(13.13x8.76)	79.1x52.8	
Mechanical Specifications		
Mount	С	
Length (mm)	278.2	
Weight (kg)	3.2	

Compatible Lighting	
Telecentric LED Lighting	DTCL-100H-xW-y
	Beam Diameter 100mm

## Notes:

- 1. Depth of Field is calculated value, this value could be used for imaging test, but to get sharp image in application, half of calculated value is suggested.
- 2. Length of I/O = WD + Length + Back Focal Length.

