

## DTCM111-170-AL

## C-mount Bi-telecentric Lens

- Optimized for 1/2.5"~1.1" C-Mount cameras;
- Largest FOV from 26mm upto 300mm;
- Excellent resolution for high pixel cameras;
- Low distortion, good telecentricity, big aperture and big depth of field for high end application.

Optical Specifications		
Magnification (x)	0.108	
Object Field of View (Фmm)	170	
Working Distance (mm)	318±5	
Max Sensor Size (Фmm)	18.4(1.1")	
Best Aperture (F/#)	6.2	
Telecentricity typical (max) (deg)	<0.1	
Distortion typical (max) (%)	<0.1	
MTF30 (lp/mm)	>150	
Depth of Field (mm)	±37.7@F11	
Length of I/O (mm)	751±5	



Field of View (mm × mm)		
1" IMX183 (13.13x8.76)		121.6x81.1
1.1" IMX253 (14.19x10.38)		131.4x96.1
Mechanical Specifications		
Mount		С
Length (mm)		415.6
Weight (kg)		6.6
Compatible Lighting		
Telecentric LED Lighting	DTCL-170-xW-y	
	Beam Diameter 170mm	

## Notes:

- 1. Depth of Field is calculated value, this value could be used for imaging test, but to get sharp image in application, half of calculated value is suggested.
- 2. Length of I/O = WD + Length + Back Focal Length.



