

## DTCM111-26-AL

## C-mount Bi-telecentric Lens

- Optimized for 1/2.5"~1.1" C-Mount cameras;
- Largest FOV from 26mm upto 300mm;
- Excellent resolution for high pixel cameras;
- Low distortion, good telecentricity, big aperture and big depth of field for high end application.

Optical Specifications		
Magnification (x)	0.708	
Object Field of View (Фmm)	26	
Working Distance (mm)	73±1	
Max Sensor Size (Фmm)	18.4(1.1")	
Best Aperture (F/#)	9.6	
Telecentricity typical (max) (deg)	<0.1	
Distortion typical (max) (%)	<0.1	
MTF30 (lp/mm)	>75	
Depth of Field (mm)	±1.6@F20	
Length of I/O (mm)	238±1	



Field of View (mm × mm)		
1" IMX183 (13.13x8.76)		18.5x12.4
1.1" IMX253 (14.19x10.38)		20.0x14.7
Mechanical Specifications		
Mount		С
Length (mm)		147.7
Weight (kg)		0.4
Compatible Lighting		
Telecentric LED Lighting	DTCL-26-xW-y	
	Beam Diameter 26mm	

## Notes:

- 1. Depth of Field is calculated value, this value could be used for imaging test, but to get sharp image in application, half of calculated value is suggested.
- 2. Length of I/O = WD + Length + Back Focal Length.

