

DTCM118-170-AL

C-mount Bi-telecentric Lens

- Optimized for 1/2.5"~1.1" C-Mount cameras;
- Largest FOV from 26mm upto 300mm;
- Excellent resolution for high pixel cameras;
- Low distortion, good telecentricity, big aperture and big depth of field for high end application.



| Optical Specifications | | |
|------------------------------------|-------------|--|
| Magnification (x) | 0.053 | |
| Object Field of View (Фmm) | 170 | |
| Working Distance (mm) | 318±5 | |
| Max Sensor Size (Фmm) | 9.0(1/1.8") | |
| Best Aperture (F/#) | 4.6 | |
| Telecentricity typical (max) (deg) | <0.1 | |
| Distortion typical (max) (%) | <0.1 | |
| MTF30 (lp/mm) | >200 | |
| Depth of Field (mm) | ±157@F11 | |
| Length of I/O (mm) | 712±5 | |

| Field of View (mm × mm) | | |
|-----------------------------|---------------------|-------------|
| 1/1.8" IMX178 (7.43x4.9) | | 140.2x92.5 |
| 1/1.8" IMX252/265 (7.1x5.3) | | 134.0x100.0 |
| Mechanical Specifications | | |
| Mount | | С |
| Length (mm) | | 376.3 |
| Weight (kg) | | 6.5 |
| Compatible Lighting | | |
| Telecentric LED Lighting | DTCL-170-xW-y | |
| | Beam Diameter 170mm | |

Notes:

- 1. Depth of Field is calculated value, this value could be used for imaging test, but to get sharp image in application, half of calculated value is suggested.
- 2. Length of I/O = WD + Length + Back Focal Length.

