

DTCM120-216-AL

C-mount Bi-telecentric Lens

- Optimized for 1/2.5"~1.1" C-Mount cameras;
- Largest FOV from 26mm upto 300mm;
- Excellent resolution for high pixel cameras;
- · Low distortion, good telecentricity, big aperture and big depth of field for high end application.

| Optical Specifications | | |
|------------------------------------|-----------|--|
| Magnification (x) | 0.037 | |
| Object Field of View (Φmm) | 216 | |
| Working Distance (mm) | 372±5 | |
| Max Sensor Size (Φmm) | 8.0(1/2") | |
| Best Aperture (F/#) | 4.2 | |
| Telecentricity typical (max) (deg) | <0.1 | |
| Distortion typical (max) (%) | <0.1 | |
| MTF30 (lp/mm) | >210 | |
| Depth of Field (mm) | ±321@F11 | |
| Length of I/O (mm) | 887±5 | |



| Field of View (mm × mm) | | |
|----------------------------|---------------------|-------------|
| 1/2.5" 9P001/31 (5.7x4.28) | | 154.1x115.7 |
| 1/2.3" 9J003 (6.44x4.62) | | 174.1x124.9 |
| Mechanical Specifications | | |
| Mount | | С |
| Length (mm) | | 497.9 |
| Weight (kg) | | 13.7 |
| Compatible Lighting | | |
| Telecentric LED Lighting | DTCL-216-xW-y | |
| | Beam Diameter 216mm | |

Notes:

- 1. Depth of Field is calculated value, this value could be used for imaging test, but to get sharp image in application, half of calculated value is suggested.
- 2. Length of I/O = WD + Length + Back Focal Length.



