

DTCM125-100H-AL

C-mount Bi-telecentric Lens

- Optimized for 1/2.5"~1.1" C-Mount cameras;
- Largest FOV from 26mm upto 300mm;
- Excellent resolution for high pixel cameras;
- Low distortion, good telecentricity, big aperture and big depth of field for high end application.

Optical Specifications		
Magnification (x)	0.072	
Object Field of View (Фmm)	100	
Working Distance (mm)	238±4	
Max Sensor Size (Фmm)	7.2(1/2.5")	
Best Aperture (F/#)	4.2	
Telecentricity typical (max) (deg)	<0.1	
Distortion typical (max) (%)	<0.1	
MTF30 (lp/mm)	>210	
Depth of Field (mm)	±84.8@F11	
Length of I/O (mm)	501±4	



Field of View (mm × mm)		
1/3" AR130/RJ33 (4.8x3.6)		66.7x50.0
1/2.5" 9P001/31 (5.7x4.28)		79.2x59.4
Mechanical Specifications		
Mount		С
Length (mm)		245.3
Weight (kg)		3.1
Compatible Lighting		
Telecentric LED Lighting	DTCL-100H-xW-y	
	Beam Diameter 100mm	

Notes:

- 1. Depth of Field is calculated value, this value could be used for imaging test, but to get sharp image in application, half of calculated value is suggested.
- 2. Length of I/O = WD + Length + Back Focal Length.

