

DTCM125-170-AL

C-mount Bi-telecentric Lens

- Optimized for 1/2.5"~1.1" C-Mount cameras;
- Largest FOV from 26mm upto 300mm;
- Excellent resolution for high pixel cameras;
- Low distortion, good telecentricity, big aperture and big depth of field for high end application.



Optical Specifications	
Magnification (x)	0.042
Object Field of View (Фmm)	170
Working Distance (mm)	318±5
Max Sensor Size (Φmm)	7.2(1/2.5")
Best Aperture (F/#)	4.2
Telecentricity typical (max) (deg)	<0.1
Distortion typical (max) (%)	<0.1
MTF30 (lp/mm)	>210
Depth of Field (mm)	±249@F11
Length of I/O (mm)	707±5

Field of View (mm × mm)		
1/3" AR130/RJ33 (4.8x3.6)		114.3x85.7
1/2.5" 9P001/31 (5.7x4.28)		135.7x101.9
Mechanical Specifications		
Mount		С
Length (mm)		371.4
Weight (kg)		6.5
Compatible Lighting		
Telecentric LED Lighting	DTCL-170-xW-y	
	Beam Diameter 170mm	

Notes:

- 1. Depth of Field is calculated value, this value could be used for imaging test, but to get sharp image in application, half of calculated value is suggested.
- 2. Length of I/O = WD + Length + Back Focal Length.

