

# DTCM125-64H-AL

## C-mount Bi-telecentric Lens

- Optimized for 1/2.5"~1.1" C-Mount cameras;
- Largest FOV from 26mm upto 300mm;
- Excellent resolution for high pixel cameras;
- Low distortion, good telecentricity, big aperture and big depth of field for high end application.



Optical Specifications	
Magnification (x)	0.113
Object Field of View (Φmm)	64
Working Distance (mm)	158±3
Max Sensor Size (Φmm)	7.2(1/2.5")
Best Aperture (F/#)	4.2
Telecentricity typical (max) (deg)	<0.1
Distortion typical (max) (%)	<0.1
MTF30 (lp/mm)	>200
Depth of Field (mm)	±34.8@F11
Length of I/O (mm)	333±3

Field of View (mm × mm)	
1/3" AR130/RJ33 (4.8x3.6)	42.5x31.9
1/2.5" 9P001/31 (5.7x4.28)	50.4x37.9
Mechanical Specifications	
Mount	C
Length (mm)	157.5
Weight (kg)	0.8
Compatible Lighting	
Telecentric LED Lighting	DTCL-64H-xW-y
	Beam Diameter 64mm

### Notes:

1. Depth of Field is calculated value, this value could be used for imaging test, but to get sharp image in application, half of calculated value is suggested.
2. Length of I/O = WD + Length + Back Focal Length.

