

## DTCM125-72-AL

C-mount Bi-telecentric Lens

- Optimized for 1/2.5"~1.1" C-Mount cameras;
- Largest FOV from 26mm upto 300mm;
- Excellent resolution for high pixel cameras;
- Low distortion, good telecentricity, big aperture and big depth of field for high end application.

Optical Specifications		
Magnification (x)	0.100	
Object Field of View ( $\Phi$ mm)	72	
Working Distance (mm)	178±3	
Max Sensor Size (Фmm)	7.2(1/2.5")	
Best Aperture (F/#)	4.2	
Telecentricity typical (max) (deg)	<0.1	
Distortion typical (max) (%)	<0.1	
MTF30 (lp/mm)	>195	
Depth of Field (mm)	±44@F11	
Length of I/O (mm)	373±3	



Field of View (mm × mm)		
1/3" AR130/RJ33 (4.8x3.6)		48.0x36.0
1/2.5" 9P001/31 (5.7x4.28)		57.0x42.8
Mechanical Specifications		
Mount		С
Length (mm)		177.5
Weight (kg)		1.0
Compatible Lighting		
Telecentric LED Lighting	DTCL-72-xW-y	
	Beam Diameter 72mm	

## Notes:

- 1. Depth of Field is calculated value, this value could be used for imaging test, but to get sharp image in application, half of calculated value is suggested.
- 2. Length of I/O = WD + Length + Back Focal Length.

