

DTCM16K-300-AL

Linescan Bi Telecentric Lens

- Optimized for large field vision system with excellent imaging quality;
- Optimized for high accuracy vision system with bitelecentric design;
- Optimized for 4K and 8K line scan cameras, support 16K line scan camera and upto 47M area cameras;
- Quality guarantee by Full test report for each lens;
- Customized Mounts, F/#, DOF Etc.



Optical Specifications	
Magnification (x)	0.197
Object Field of View (Φmm)	300
Working Distance (mm)	465±6
Max Sensor Size (Φmm)	59
Best Aperture (F/#)	9
Telecentricity typical (max) (deg)	<0.1
Distortion typical (max) (%)	<0.1
MTF30 (lp/mm)	>95
Depth of Field (mm)	±20.6@F20
Length of I/O (mm)	1268±6

Field of View (mm × mm)	
48.7×29.0 with KAI-47051	247.2×147.2
57.4mm with 16K×3.5/3.53um	291.4mm
57.4mm with 8K×7um/7.04um	291.4mm
Mechanical Specifications	
Mount	M72
Length (mm)	791.0
Weight (kg)	48.0
Compatible Lighting	
Telecentric LED Lighting	DTCL-300-xW-y Beam Diameter 300mm

Notes:

1. Depth of Field is calculated value, this value could be used for imaging test, but to get sharp image in application, half of calculated value is suggested.
2. Length of I/O = WD + Length + Back Focal Length.

