

DTCM210-258-M58-AL

Large Format Bi-telecentric Lens

- Optimized for 4/3"~44mm M-mount or other mount cameras;
- FOV from 26mm upto 300mm;
- High resolution, low distortion and homogeneous image quality;
- Full test report for each units are provided;
- Customized mounts available.

| Optical Specifications | | |
|------------------------------------|-----------|--|
| Magnification (x) | 0.128 | |
| Object Field of View (Φ mm) | 258 | |
| Working Distance (mm) | 338±5 | |
| Max Sensor Size (Фmm) | 33(2") | |
| Best Aperture (F/#) | 7.8 | |
| Telecentricity typical (max) (deg) | <0.1 | |
| Distortion typical (max) (%) | <0.1 | |
| MTF30 (lp/mm) | >110 | |
| Depth of Field (mm) | ±39.1@F16 | |
| Length of I/O (mm) | 867±5 | |



| Field of View (mm × mm) | | |
|---------------------------|-------|-------------|
| 2" DALSA 12M (24.58x18 | .43) | 192.0x144.0 |
| 2" PYTHON 25K (23.04x23 | 3.04) | 180.0x180.0 |
| Mechanical Specifications | | |
| Mount | | F or other |
| Length (mm) | | 482.4 |
| Weight (kg) | | - |
| Compatible Lighting | | |
| Telecentric LED Lighting | | LP270-90 |

Notes:

- 1. Depth of Field is calculated value, this value could be used for imaging test, but to get sharp image in application, half of calculated value is suggested.
- 2. Length of I/O = WD + Length + Back Focal Length.

