

DTCM71M-120H-M58-AL

Large Format Bi-telecentric Lens

- Optimized for 4/3"~44mm M-mount or other mount cameras;
- FOV from 26mm upto 300mm;
- High resolution, low distortion and homogeneous image quality;
- Full test report for each units are provided;
- Customized mounts available.

| Optical Specifications | | |
|------------------------------------|----------|--|
| Magnification (x) | 0.325 | |
| Object Field of View (Φ mm) | 120 | |
| Working Distance (mm) | 273±5 | |
| Max Sensor Size (Фmm) | 39 | |
| Best Aperture (F/#) | 7.6 | |
| Telecentricity typical (max) (deg) | <0.1 | |
| Distortion typical (max) (%) | <0.1 | |
| MTF30 (lp/mm) | >115 | |
| Depth of Field (mm) | ±6.1@F16 | |
| Length of I/O (mm) | 670±5 | |



| Field of View (mm × mm) | | | |
|---------------------------|---------------------|-----------|--|
| CHR 70M (31.0x21.7 | 7) | 95.4x66.8 | |
| Mechanical Specifications | | | |
| Mount | | M58 | |
| Length (mm) | | 350 | |
| Weight (kg) | | 4.8 | |
| Compatible Lighting | | | |
| Telecentric LED Lighting | DTCL-120-xW-y | | |
| | Beam Diameter 120mm | | |

Notes:

- 1. Depth of Field is calculated value, this value could be used for imaging test, but to get sharp image in application, half of calculated value is suggested.
- 2. Length of I/O = WD + Length + Back Focal Length.

