

WWK15-110C-111

Large FOV Objective Telecentric Lens

- Object side telecentric lens, support 5Mp-20Mp area scan camera.
- High definition, low distortion, good telecentricity, especially suitable for high-precision AOI and positioning applications.
- Built-in coaxial lighting, especially suitable for inspection of wafers, glass devices.
- Quickly customization apply to different camera specifications, as well as magnification, working distance, DOF requirements.

Optical Specifications	
Magnification (x)	1.5
Working Distance (mm)	110±2
Max Sensor Size (Фmm)	18.0(1.1")
Best Aperture (F/#)	10
Telecentricity typical (max) (deg)	<0.1
Distortion typical (max) (%)	<0.1
MTF30 (lp/mm)	>78
NA	0.0747
Resolution (µm)	4.5
Depth of Field (mm)	±0.35@F20
Length of I/O (mm)	256±2



Field of View (mm \times mm)	
1" IMX183 (13.13x8.76)	8.8x5.8
1.1" IMX253 (14.19x10.38)	9.5x6.9
Mechanical Specifications	
Mount	С
Length (mm)	128.8
Weight (kg)	-
Coaxial Light	Yes
Iris	No

Notes:

1. Depth of Field is calculated value, this value could be used for imaging test, but to get sharp image in application, half of calculated value is suggested.

2. Length of I/O = WD + Length + Back Focal Length.

