

WWK40-108-111V3

Large FOV Objective Telecentric Lens

- Object side telecentric lens, support 5Mp-20Mp area scan camera.
- · High definition, low distortion, good telecentricity, especially suitable for highprecision AOI and positioning applications.
- · Built-in coaxial lighting, especially suitable for inspection of wafers, glass devices.
- Quickly customization apply to different camera specifications, as well as magnification, working distance, DOF requirements.

Optical Specifications	
Magnification (x)	4.0
Working Distance (mm)	108±2
Max Sensor Size (Φmm)	18.0(1.1")
Best Aperture (F/#)	20
Telecentricity typical (max) (deg)	<0.05
Distortion typical (max) (%)	<0.07
MTF30 (lp/mm)	43
Resolution (µm)	43
Depth of Field (mm)	±0.05@F20



Field of View (mm × mm)	
1" IMX183 (13.13x8.76)	3.3x2.2
1.1" IMX253 (14.19x10.38)	3.5x2.6
Mechanical Specifications	
iviechanicai Specifica	ations
Mount	c C

Notes:

- 1. Depth of Field is calculated value, this value could be used for imaging test, but to get sharp image in application, half of calculated value is suggested.
- 2. Length of I/O = WD + Length + Back Focal Length.



