

## WWK80-108-111V3

## Large FOV Objective Telecentric Lens

- Object side telecentric lens, support 5Mp-20Mp area scan camera.
- · High definition, low distortion, good telecentricity, especially suitable for highprecision AOI and positioning applications.
- · Built-in coaxial lighting, especially suitable for inspection of wafers, glass devices.
- Quickly customization apply to different camera specifications, as well as magnification, working distance, DOF requirements.

| Optical Specifications             |              |
|------------------------------------|--------------|
| Magnification (x)                  | 8.0          |
| Working Distance (mm)              | 108±2        |
| Max Sensor Size (Φmm)              | 18.0(1.1")   |
| Best Aperture (F/#)                | 40.4         |
| Telecentricity typical (max) (deg) | <0.02        |
| Distortion typical (max) (%)       | <0.08        |
| MTF30 (lp/mm)                      | 21           |
| Resolution (µm)                    | 21           |
| Depth of Field (mm)                | ±0.025@F40.4 |



| Field of View (mm × mm)   |         |
|---------------------------|---------|
| 1" IMX183 (13.13x8.76)    | 1.6x1.1 |
| 1.1" IMX253 (14.19x10.38) | 1.8x1.3 |
| Mechanical Specifications |         |
| Mechanical Specification  | ations  |
| Mechanical Specification  | c C     |
| •                         |         |

## Notes:

- 1. Depth of Field is calculated value, this value could be used for imaging test, but to get sharp image in application, half of calculated value is suggested.
- 2. Length of I/O = WD + Length + Back Focal Length.



